REMS dies

The proven, indestructible REMS quality dies with precise cutting geometry ensure an excellent start-cutting performance, easy threading and clean threads. Dies in a high-quality special-grade steel, fully tempered and hardened, for extremely long die life.

Thread type	Size	Art.-No.
Pipe threads R tapered, right-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛ R ¼ R ⅜ R ½ R ¾ R 1 R 1¼ R 1½ R 2	521002RWS 521012RWS 521022RWS 521032RWS 521042RWS 521052RWS 521062RWS 521072RWS 521082RWS
Pipe threads R tapered, left-hand ISO 7-1, EN 10226 (DIN 2999, BSPT)	R ⅛ LH R ¼ LH R ⅜ LH R ½ LH R ¾ LH R 1 LH R 1¼ LH R 1½ LH R 2 LH	521102RWS 521112RWS 521122RWS 521132RWS 521142RWS 521152RWS 521162RWS 521172RWS 521182RWS
Pipe threads NPT tapered, right-hand Taper Pipe Thread ASME B1.20.1	NPT ⅛ NPT ¼ NPT ⅜ NPT ½ NPT ¾ NPT 1 NPT 1¼ NPT 1½ NPT 2	521202RWS 521212RWS 521222RWS 521232RWS 521242RWS 521252RWS 521262RWS 521272RWS 521282RWS
Threads M for electric conduit EN 60423	M 16 × 1.5 M 20 × 1.5 M 25 × 1.5 M 32 × 1.5 M 40 × 1.5 M 50 × 1.5	521302RWS 521312RWS 521322RWS 521332RWS 521342RWS 521352RWS



German Quality Product

Info